

IN THE CLAIMS:

Claims ~~1-34~~ (Canceled).

35. (Currently Amended) A process for determining the risk of flammability of a mixture of at least two reactive gases A, B, in an inert or base gas, or the order of mixing of these reactive gases into the inert or base gas, the process comprising:

- a step of determining whether the composition of the mixture, during its formation, passes through ~~the~~ a flammability region in the ternary diagram of the A/B/inert or base gas mixture when the mixture is produced according to a first mode in which A is first mixed into the inert or base gas to form a first mixture and then B is mixed into the first mixture to form the final mixture;

= a step of determining a first transit time through the flammability region of the ternary diagram when the mixture is produced according to the first mode; and

= a step of comparing the first transit time with the chemical induction time of the mixture or of the stoichiometric mixture.

36. (Canceled)

37. (Previously Added) The process according to claim 35, further comprising a step of comparing one or more mixing times of the mixer or mixers used with the chemical induction time of the mixture or of the stoichiometric mixture.

38. (Currently Amended) The process according to ~~one of~~ claim 35, further comprising, if the composition of the mixture passes through the flammability region of the ternary diagram, or if the first transit time or the mixing time is greater than the chemical induction time of the mixture:

- a step of determining whether the composition of the mixture, during its formation, passes through the flammability region in the ternary diagram of the A/B/inert or base gas mixture, when the latter is produced according to a second mode in which B is first mixed into the inert or base gas to form a first mixture and then A is mixed into the first mixture to form the final mixture.

39. (Previously Added) The process according to claim 38, further comprising:

- a step of determining a second transit time through the flammability region of the ternary diagram when the mixture is produced according to the second mode;
- a step of comparing the second transit time with the chemical induction time of the mixture or of the stoichiometric mixture.

40. (Previously Added) The process according to claim 38, further comprising a step of comparing one or more mixing times of the mixer(s) used with the chemical induction time of the mixture or of the stoichiometric mixture.

41. (Previously Added) The process according to claim 35, wherein, if the composition of one of the mixtures according to one of the modes of injection does not pass through the flammability region during its formation, this mode is selected.

42. (Currently Amended) The process according to claim ~~36~~ 35, wherein a mode or the mode for which the mixing time or times or the transit time through the flammability region of the ternary diagram is less than the chemical induction time of the mixture is selected.

43. (Previously Added) The process according to claim 35, wherein, if the two modes of injection both force the composition to pass through the flammability region, selecting of the mode for which:

- (i) the intermediate mixture point, representative of the composition of the first mixture, lies outside the flammability region;
- (ii) the mixing time or times or the transit time through the flammability region of the ternary diagram is less than the chemical induction time of the mixture.

44. (Previously Added) A process for producing a mixture of at least two reactive gases A, B in an inert or base gas, comprising:

- determining the flammability risk of the mixture, while the mixture is being produced, or determining the order of mixing of the reactive gases into the inert or base gas, according to claim 35;

- mixing the reactive gases A and B in the order for which the composition of the mixture does not pass through the flammability region while the composition is changing, or for which the mixing time(s) or the transit time through the flammability region of the ternary diagram is (are) less than the chemical induction time of the mixture.

45. (Previously Added) A process for producing a final mixture of at least two reactive gases A, B in an inert or base gas, comprising:

- mixing the gas A in the inert or base gas, to form a first mixture, the composition of which changes, during its formation, outside the flammability region of the ternary diagram of the A/B/inert gas mixture, or passes through the flammability region with one or more mixing times of the mixer(s) used, or a transit time through the flammability region, less than the chemical induction time of the first mixture;

- mixing the gas B into the first mixture, forming a mixture whose composition changes towards that of the final mixture, the composition of the mixture changing, in the ternary diagram, either without passing through the flammability region or by passing through the flammability region, with one or more mixing times of the mixer(s) used, or a transit time through the flammability region, less than the chemical induction time of the mixture.

46. (Previously Added) The process according to claim 35, further comprising a prior step of determining the mixing time or times of one or more

mixers intended to be used for mixing reactive gases and for determining the temperature at which the spontaneous ignition time of the mixture becomes equal or substantially equal to one of the mixing times.

47. (Previously Added) The process according to claim 35, wherein the mixing is carried out at a temperature of between 300°C and 600°C.

48. (Previously Added) The process according to claim 35, wherein the mixing of the two reactive gases A, B into an inert or base gas is that of a recycle process.

49. (Previously Added) The process according to claim 35, wherein the mixture of the reactive gases is a mixture of oxygen and butane in an inert gas.

50. (Previously Added) The process according to claim 35, wherein the mixture of the reactive gases is a mixture of oxygen and ethylene in an inert gas.

51. (Previously Added) The process according to claim 35, wherein the reactive gases to be mixed into the inert or base gas are at least three in number and the order of mixing of the gases is determined by considering the pairs of gases that can be mixed successively, and the corresponding ternary diagrams.

52. (Previously Added) The process according to claim 35, further comprising a step of consulting an electronic database containing data on ternary diagrams and/or consulting an electronic database containing data on induction times of gas mixtures and/or consulting an electronic database containing data on mixing times of mixers.

53. (Previously Added) The process according to claim 35, further comprising a graphical representation on a display screen, of the ternary diagram(s) in question and of the corresponding flammability region(s) in this diagram(s).

54. (Previously Added) A process for producing a plant for mixing at least two reactive gases A, B into a base gas, comprising:

- determining the order of mixing the gases according to claim 35; and
- producing a plant so as to mix the gases in the order thus determined.

55. (Currently Amended) Apparatus for establishing the flammability risk of gas mixtures, each mixture comprising at least two reactive gases A, B, in an inert or base gas, or for determining the order of mixing of the reactive gases into the inert or base gas, comprising:

- means for storing at least one database containing, for gas mixtures, data on the ternary diagrams of the mixtures, and the flammability regions in the diagrams for given temperature and pressure conditions;

- B1
- means for selecting a gas mixture and temperature and pressure conditions to be used for the gas mixture;
 - means for displaying a ternary diagram and the flammability region of a mixture in the diagram;
 - = means for computing or establishing, for gas mixtures containing at least two reactive gases A, B in an inert or base gas, and for temperature and pressure conditions of these gases, a transit time for the mixture to pass through the flammability region of the corresponding ternary diagram; and
 - = means for storing at least one database containing, for gas mixtures, data on the induction times, or ignition times, of these mixtures according to the temperature and pressure conditions.

Claims 56-58 (Canceled).

59. (Previously Added) The apparatus according to claim 55, further comprising means for computing, or especially means programmed for computing or establishing, for gas mixtures each containing at least two reactive gases A, B in an inert or base gas, and according to temperature and pressure conditions of these mixtures, chemical induction times of these mixtures.

60. (Previously Added) The apparatus according to claim 55, further comprising a database containing information on mixing times of mixers, and means for selecting a mixer.

61. (Previously Added) The apparatus according to claim 55, further comprising means for, or means especially programmed for, comparing a mixing time or a transit time through a flammability region of one of the ternary diagrams, and a chemical induction time of this mixture.

62. (Previously Added) Apparatus for establishing the flammability risk of mixtures, wherein each mixture includes at least two reactive gases A, B in an inert or base gas, or for establishing the order of mixing of these reactive gases into the inert or base gas, comprising means for computing, or means especially programmed for computing, as a function of temperature and pressure conditions:

- the ternary diagram of a mixture and the flammability region in the diagram;
- a chemical induction time of the mixtures.

63. (Previously Added) The apparatus according to claim 62, further comprising means for displaying a ternary diagram and the flammability region of a mixture in the diagram.

64. (Previously Added) The apparatus according to claim 62, further comprising means for computing a mixing time of a given mixer or for storing mixing times of a set of mixers.

65. (Canceled)

66. (Previously Added) A computer program comprising the instructions for executing a process according to claim 35.

67. (Previously Added) A data medium, which can be read by a computing system, comprising the data, in coded form, for executing a process according to claim 35.

68. (Previously Added) A software product comprising a program data medium means, capable of being read by a computing system, allowing a process according to claim 35 to be executed.
